

[11]

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ : A61L 2/20, B65B 55/10	A1	(11) International Publication Number: WO 98/16259 (43) International Publication Date: 23 April 1998 (23.04.98)
(21) International Application Number: PCT/SE97/01575 (22) International Filing Date: 19 September 1997 (19.09.97) (30) Priority Data: 9603735-3 14 October 1996 (14.10.96) SE (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE S.A. [CH/CH]; Avenue Général-Guisan 70, CH-1009 Pully (CH). (72) Inventor; and (75) Inventor/Applicant (for US only): BJERBORN, Thomas [SE/SE]; Vårvädersgatan 6B, S-222 27 Lund (SE). (74) Agents: PETRI, Stellan et al.; Ström & Gulliksson AB, P.O. Box 4188, S-203 13 Malmö (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>With amended claims.</i> <i>In English translation (filed in Swedish).</i>
(54) Title: A METHOD OF STERILIZING A PACKAGE MATERIAL (57) Abstract <p>Containers which are ready to be filled or a package material having a plastic surface can be sterilized by hydrogen peroxide in gaseous phase being supplied to the previously heated plastic surface, the entire sterilization procedure being performed with the hydrogen peroxide in gaseous phase.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A METHOD OF STERILIZING A PACKAGE
MATERIAL

The present invention refers to a method of steril-
5 izing a package material. More precisely the invention
refers to a method of sterilizing a package material having
a plastic surface by means of hydrogen peroxide in gaseous
phase being supplied to the previously heated plastic
surface.

10 Sterile containers which are ready to be filled can
be obtained in various ways. One method of sterilization
implies that the plastic containers are sealed directly in
connection with the manufacturing procedure, e.g. when blow
moulded. Due to the collapse of the container at a sub-
15 sequent lowering of the temperature the sealing in this
case results in considerable problems. The container must
therefore be stored at an elevated temperature since the
volume of air enclosed in the container will decrease if
the temperature is decreased. Such a storage is both
20 cumbersome and costly. In order to avoid this, among other
materials hydrogen peroxide is nowadays utilized in a
liquid or gaseous phase, the inside of the containers then
being sterilized.

Hydrogen peroxide is a very potent but not especially
25 stable oxidant, and an advantage is that only plain water
is formed as by-product. However, the half-life of hydrogen
peroxide is very long, and the sterilizing agent has thus
to be removed after it has been allowed to exert its
effect.

30 Hydrogen peroxide is supposed to exert its anti-
microbial activity through its powerful oxidizing effect
by acting on components in the cytoplasmic membrane of the
microorganisms. In the sterilizing procedure hydrogen
peroxide is used as a water solution which is sprayed into
35 a container. When the container is subsequently heated the

hydrogen peroxide is gasified and can be ventilated away after having exerted its effect.

According to an alternative sterilizing procedure a container is in a first step subjected to hydrogen peroxide in gaseous phase, which is allowed to condensate on the inside of the container. By this procedure a homogeneous coating of hydrogen peroxide is obtained, which completely covers the package material. In a subsequent step the condensed gas is again gasified and is finally ventilated away. By this procedure an acceptable death rate of micro-organisms for commercial sterilization can be achieved.

When for example plastic containers are sterilized these are in practice coated with a commercial standard solution, called "Oxonia Aktiv", which among other things contains hydrogen peroxide and peracetic acid. The solution is allowed to act for some minutes, and the containers are then rinsed with clean sterile water. Such a procedure is both complicated and time consuming.

A further problem is that with certain plastics in the package material, above all polyester, residues of hydrogen peroxide are obtained which are adsorbed on the inside of the container as a result of spraying, coating or condensation. They can afterwards have a negative influence on the filling material, for example by changing the colour. The authorities have established limit values which must not be exceeded for residues of hydrogen peroxide.

It is rather unusual to treat such a package material as a polyester aseptically since this type of material mostly is used for soft drinks and the like. However, there exists a great interest from the market for an aseptic bottle of polyethylene terephthalate (PET).

In order to minimize the risk of residual product formation the hydrogen peroxide can be ventilated away, e.g. at the elevated temperature or by sterile air being blown into the container. Such a procedure is costly and it

would thus be desirable if shorter ventilation times could be used, which would result in a lower cost per container.

The purpose of the invention is to eliminate or reduce the drawbacks mentioned above which arise during a sterilization by means of hydrogen peroxide according to the state of the art.

In order to achieve this purpose the method according to the invention has obtained the characterizing features of claim 1.

A sterilizing process with a condensation of hydrogen peroxide comprises four phases of different time intervals: a heating phase, a gassing phase, a holding phase, and a ventilation phase.

During the heating phase the container is heated to a suitable temperature. The heating phase is not necessary. However, it reduces the amount of condensate which later on has to be ventilated away.

During the gassing phase gaseous hydrogen peroxide is injected into the previously heated container and over the surface which is to be exposed to the treatment, onto which the gas condensates, and a condensate in the form of droplets is formed. The gas used is a mixture of air and a gasified solution of hydrogen peroxide. The solution of hydrogen peroxide is supplied as a commercial grade which consists of about 65 % water and about 35 % hydrogen peroxide. However, other concentrations can of course be used in dependence of other parameters.

During the holding phase the condensate is allowed to exhibit its effect, and during the ventilation phase the container is ventilated, the condensate again being transformed into gaseous phase and removed from the container. In this connection hot air is used which has been prefiltered and sterilized by means of filtration.

Experiments were performed with the purpose of achieving an equally effective sterilization as that which

allows the hydrogen peroxide used to exert its effect in the form of a condensated gas. In these experiments the hydrogen peroxide was according to the invention allowed to remain in the gaseous phase during the entire sterilization
5 procedure.

In comparison with the sterilization by means of condensation described above the method according to the invention implies briefly that the containers are sterilized with gasified hydrogen peroxide, the containers first
10 being heated to a temperature which is higher than the dew point of the gas used. The containers are then blown to dryness with hot sterile air.

During the sterilization procedure the containers are thus for a certain period of time exposed to gaseous
15 hydrogen peroxide of a specific temperature, dew point and flow rate. Apart from the hydrogen peroxide concentration these parameters are important in order to achieve an effective killing. In this connection the dew point is the temperature the gaseous hydrogen peroxide must be cooled to
20 in order to obtain a condensation, a water solution of hydrogen peroxide being separated. This temperature is dependent on the hydrogen peroxide content in the gas. The dew point is adjusted to be used in an existing sterilizing equipment.

25 Preliminary experiments have shown that the amount of residual hydrogen peroxide per unit area varied after contact with different types of package material. Certain problems were obtained with polyester as a package material, and thus the experiments were concentrated on such a
30 material by using bottles of polyethylene terephthalate. However, other types of containers which are ready to be filled were also studied.

Example 1. Comparison between sterilizing effects.

A comparison was performed between the sterilizing effect achieved by means of gassing/condensation and that with gassing alone according to the invention. The efficiency with regard to killing microorganisms in the form of a logarithmic reduction was defined as the number of organisms in a reference sample minus the number of surviving organisms.

PET bottles were inoculated with spores of *Bacillus subtilis* NCA 7252, and after the respective sterilization treatment the results were statistically evaluated with a conventional procedure (based on the method with "Most Probable Number") which is well known to the man skilled in the art.

The containers to be subjected to gassing/condensation or gassing alone according to the invention, respectively, received the same treatment during the gassing phase and the holding phase, which treatment by way of earlier experiments had been found to be optimal.

Thus, in the sterilization procedure a gassing phase of 3 sec was used with gaseous hydrogen peroxide, the gas having a temperature of 90 °C, a dew point of 65 °C, and a flow rate of 40 kg/h. The length of the holding phase was 1 sec.

Those containers which should be subjected to gassing/condensation were during the heating phase heated to 50-55 °C, and the containers were ventilated for 10 sec with sterile air of 70 °C having a flow rate of 40 kg/h. During the gassing/condensation the ventilation time was adjusted in such a way that all visible condensate had evaporated. Those containers which had been subjected to gassing alone according to the invention were during the heating phase subjected to a temperature of 70-80 °C, and during the ventilation phase the containers were fluxed for 2 sec with sterile air of 80 °C at a flow rate of 60 kg/h.

The results indicated that a sufficient killing effect was achieved in the form of a logarithmic reduction of at least $\log 5$ (10^5) with both sterilizing methods.

5 **Example 2.** Comparison between evolved residual amounts.

Experiments were performed in order to study if any residues were obtained in PET containers sterilized according to the invention. At the same time a comparison was performed with polyethylene (PE) bottles.

10 Bottles of PET and PE were subjected to the same sterilization treatment as in Example 1 apart from that the time after the filling of the bottles, the storage time, was varied and that the ventilation time after the two sterilization procedures was 2 sec. Residual hydrogen
15 peroxide in each container was measured by means by a vial HP-10 (Chemetrics, 90298-31) according to the instructions of the manufacturer. The results obtained are shown i Table 1.

20 **Table 1.** Residual hydrogen peroxide (ppm) after sterilization (2 sec ventilation time).

		Material			
		PE	PET		
25	Storage time (min)	5	10	30	90
	Gassing	0.5	3	3	3
	Condensation	-	10	>10	-

The results show that no significant residual hydro-
30 gen peroxide was obtained with polyethylene. It is also possible to reduce residual hydrogen peroxide to an acceptable level in a PET container which has been subjected to gassing according to the invention and then ventilated for such a short ventilation time as 2 sec. About 3 times more
35 residuals are obtained in a PET bottle sterilized by means of condensation. This tendency is maintained even with such a short ventilation time as 15 sec (Table 2).

according to the invention. In this connection the package material may well be treated continuously.

CLAIMS

1. Method of sterilizing a plastic surface by hydrogen peroxide in gaseous phase being supplied to the
5 previously heated plastic surface, c h a r a c t e r -
i z e d in that the entire sterilization procedure is performed with the hydrogen peroxide in gaseous phase.

2. Method as claimed in claim 1, c h a r a c -
t e r i z e d in that the plastic surface is heated to a
10 temperature which is higher than the dew point for the hydrogen peroxide in gaseous phase.

3. Method as claimed in claim 1, c h a r a c -
t e r i z e d in that the plastic surface comprises a polyester.

15 4. Method as claimed in claim 3, c h a r a c -
t e r i z e d in that the plastic surface comprises polyethylene terephthalate.

AMENDED CLAIMS

[received by the International Bureau on 11 March 1998 (11.03.98);
original claims 1-4 replaced by new claims 1-5 (1 page)]

1. Method of sterilizing a plastic surface by hydrogen peroxide in gaseous phase being supplied to the previously heated plastic surface, c h a r a c t e r - i z e d in that the entire sterilization procedure is performed with the hydrogen peroxide in gaseous phase and that the plastic surface is heated to a temperature which is higher than the dew point for the hydrogen peroxide in gaseous phase.
2. Method as claimed in claim 1, c h a r a c - t e r i z e d in that the plastic surface comprises a polyester.
3. Method as claimed in claim 1, c h a r a c - t e r i z e d in that the plastic surface comprises polyethylene terephthalate.
4. Method as claimed in claim 1 of sterilizing a package material for a container, c h a r a c t e r - i z e d in that the package material having a plastic surface is sterilized before the container has obtained its final form.
5. Method as claimed in claim 4, c h a r a c - t e r i z e d in that the package material having a plastic surface is sterilized continuously.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01575

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61L 2/20, B65B 55/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0384535 A2 (SHIKOKU KAKOKI CO., LTD.), 29 August 1990 (29.08.90), figures 1-6, claims 1-7 --	1,3,4
X	EP 0481361 A1 (FMC CORPORATION), 22 April 1992 (22.04.92), figures 1-5, claims 1-12 --	1,3,4
X	US 4797255 A1 (K. HATANAKA ET AL.), 10 January 1989 (10.01.89), figures 1-6, claims 1-4 -----	1,3,4



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 March 1998

Date of mailing of the international search report

05-03-1998

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Agneta Änggård

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

03/02/98

International application No.
PCT/SE 97/01575

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0384535 A2	29/08/90	AU 617591 B AU 5003690 A JP 2220663 A	28/11/91 30/08/90 03/09/90
EP 0481361 A1	22/04/92	AU 644904 B AU 8570591 A CA 2053395 A DE 69105907 D GB 2248551 A JP 2529909 B JP 7033122 A MX 173900 B NZ 240157 A US 5178841 A	23/12/93 16/04/92 14/04/92 00/00/00 15/04/92 04/09/96 03/02/95 07/04/94 27/06/94 12/01/93
US 4797255 A1	10/01/89	CA 1276426 A DE 3789158 D,T EP 0243003 A,B SE 0243003 T3 JP 1870828 C JP 63011163 A	20/11/90 06/10/94 28/10/87 06/09/94 18/01/88

Table 2. Residual hydrogen peroxide (ppm) after sterilization (15 sec ventilation time).

Storage time (min)	Material		
	PE	PET	PET
5	5	30	250
Gassing	0	0.3	0.1
Condensation	0	0.8	0.2

Thus, when gassing according to the invention low residual amounts were obtained of the sterilization medium hydrogen peroxide used together with an effective killing. This reduction in the number of microorganisms can also be increased by increasing the dew point (the gas concentration) or by prolonging the gassing phase. However, if the dew point is increased too much the residual amounts will increase with the gassing procedure according to the invention.

The sterilization method according to the invention is preferably intended to be used for sterilizing containers which are ready to be filled and/or for a package material having a plastic surface which can comprise a polyester, e.g. polyethylene terephthalate. However, the method is not limited to containers which are ready to be filled. On the contrary, it is an advantage if a container is sterilized as a "preform", i.e. before it - for example by means of blow moulding - has obtained its final form which has a difficult geometry from a sterilizing point of view. In this case smaller residual amounts per unit area will be obtained in the completed container. The package material in the form of a sheet or a web can thus in the same way as a container which is ready to be filled be subjected to the above mentioned four phases, heating phase, gassing phase, holding phase, and ventilation phase, the sterilization being effected by means of the method